

Printing date: 29.07.2019 Revision: 0 /14.01.2019 Page 1 / 6

1. Identification of the substance / mixture and of the company / undertaking

Trade name: MAGNUM® FINECUT, 1.0 mm thickness, cutting disc

Supplier: Gerd Eisenblätter GmbH

Jeschkenstaße 12d 82538 Geretsried

Phone: +49 (0) 8171 / 9082 - 010

Emergencies: +49 (0) 8171 / 9082 - 010

2. Hazards identification

2.1. Classification

Not applicable

Abrasives are articles and not dangerous substances or mixtures according to Regulation (EC) N° 1272/2008.

See also section 8 and 16.

2.2. Label elements

Abrasives are articles and not dangerous substances or mixtures and therefore no labelling is required according to Regulation (EC) N° 1272/2008.

2.3. Other hazards

Not known.

3. Composition / information on ingredients

The products contain the following ingredients which are classified according to Regulation (EC) Nr. 1272/2008 or for which a community occupational exposure limit value exists:

Substance	EC-N°	CAS-N°	REACH Registration N°	Conc. (%)	Classification acc. to (EC) N° 1272/2008 Hazard classes/ hazard categories	
Aluminium potassium fluoride	262-153-1	60304-36-1	01-2119513404-51	3 - 8	Acute Tox. 4 Eye Irrit. 2 Repr. 2 STOT RE 1 Aquatic Chronic 2	H 332 H319 H362 H372 H 412

(For full text of H- and R-phrases see section 16)



Trade Name: MAGNUM® FINECUT Page 2 / 6

4. First aid measures

See also section 8 and 16

4.1. Description of first aid measures

Inhalation: Not possible, due to the form of the products

Eye contact: Not possible, due to the form of the products

Skin contact: No harmful effects known

Ingestion: Not likely, due to the form of the products; if necessary contact physician

Note to physician: Not available.

4.2. Most important symptoms and effects, both acute and delayed

Not known.

4.3. Indication of any immediate medical attention and special treatment needed

Not relevant. Treat symptomatically.

5. Fire fighting measures

5.1. Extinguishing media

Extinguishing media: water, foam, sand, powder or CO2 as appropriate for surrounding materials

5.2. Special hazards arising from the products

Toxic fumes may occur. Use respiratory protective equipment.

5.3. Advice for fire fighters

Extinguishing materials should be selected according to the surrounding area.

6. Accidental release measures

Not applicable.

7. Handling and storage

Follow instructions of grinding machine manufacturers and the relevant national regulations. In addition, observe the safety recommendations of the manufacturer.

Store abrasives in dry, frost-free conditions avoiding wide variations in temperature. Ensure they are properly protected and supported to prevent damage und distortion.



Trade Name: MAGNUM® FINECUT Page 3 / 6

8. Exposure controls / personal protection

8.1. Control parameters

Before grinding it is recommended to perform a risk assessment and to use personal protection equipment accordingly.

Occupational exposure limit values and/or biological limit values

Keep exposure to the following components under surveillance. (Observe also the regional official regulations)

Limit value type	substance	EC-N°	CAS-N°	Occupational limit value			Peak limit	source, remark	
(country of origin)				Long term		Short term			
				mg/m³	ml/m³ (ppm)	mg/m³	ml/m³ (ppm)		
	aluminium potassium fluoride	262-153-1	60304-36-1	•					HSL, (fluorides, inorganic as F)
European Union		**	W						

^{*}Valid for UK, other countries: observe national values (please see attachment "International Limit Values", page 7)

Note: Hazardous dust of the workpiece material may be generated during grinding and/or sanding operations. National regulations for dust exposure limit values have to be taken into consideration.

8.2. Exposure controls

- 8.2.1. Individual protection measures
- 8.2.1.1. Respiratory protection: Use respiratory protective equipment (type depends on specific application and material being ground)
- 8.2.1.2. Hand protection: Wear protective gloves (type depends on specific application and material being ground)
- 8.2.1.3. Eye protection: Wear protective goggles or face shield (type depends on specific application and material being ground)
- 8.2.1.4. Hearing protection: Use hearing protection (type depends on specific application and material being ground)
- 8.2.1.5. Body protection: Use protective clothing (type depends on specific application and material being ground)

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

9.1.1 Physical state: solid

9.1.2 Colour: according to the type of product

9.1.3 Solubility in water: not measured

9.2. Other Information

None



Trade Name: MAGNUM® FINECUT Page 4 / 6

10. Stability and reactivity

10.1. Reactivity

Organic coated abrasives are stable when handled or stored correctly.

10.2. Chemical stability

No decomposition in normal use.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

Organic coated abrasives are stable when handled or stored correctly.

10.5. Incompatible materials

No dangerous reactions known.

10.6. Hazardous decomposition products

At temperatures exceeding 250° C hazardous or toxic decomposition products may be generated.

11. Toxicological information

11.1. Information on toxicological effects

No toxicological effects if inhaled or swallowed or with eye or skin contact are known.

See also section 8.

12. Ecological information

12.1. Toxicity

No effects known.

12.2. Persistence and degradability

No biodegradable potentials known.

12.3. Bioaccumulative potential

No potentials known.

12.4. Mobility in soil

No potentials known.

12.5. Results of PBT and vPvB assessment

Not relevant.

12.6. Other adverse effects

No effects known.

13. Disposal considerations

13.1. Waste treatment methods



Trade Name: MAGNUM® FINECUT Page 5 / 6

13.1. Product

Follow national and regional regulations.

- O Due to the ingredients and properties disposal as non hazardous waste (2000/532/EC) is possible if no hazardous materials are added to the abrasives. (EWC Nr. 120121),
- X Due to the ingredients and properties disposal as hazardous waste (2000/532/EC) (EWC Nr. 120120)

13.2. Packing

Follow national and regional regulations.

14. Transport information

The products are not covered by international regulation on the transport of dangerous goods.

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the products

No specific labelling requirements under respective EC directives.

15.2. Chemical safety assessment

Not relevant.

16. Other information

Changes to the previous versions

See sections 1 to 16.

Literature and data sources

REACH Regulation (EC) Nr. 1907/2006 Regulation (EC) N° 1272/2008 Directive 98/24/EC

Directive 90/24/EC

Directive 2000/39/EC

Directive 75/324/EEC

Decision 2000/532/EC

Transport regulations according to ADR, RID und IATA.

Hazard statements referred to in section 2 and 3

According to Regulation (EC) N° 1272/2008:

Hazard statements for aluminium potassium flouride

H 332 Harmful if inhaled

H 319 Causes serious eye irritation

H 362 May cause harm to breast-fed babies

H 372 May cause damage to organs (lung, skeleton) to prolonged or repeated exposure

H 412 Harmful to aquatic life with long lasting effects



Trade Name: MAGNUM® FINECUT Page 6 / 6

International Limit Values *

Substance: Fluoride (inorganic as F) CAS No. 16984-48-8

Countries	Limit value – Eight hours ,	Limit value – Short term			
	mg/m³	mg/m ³			
Austria	2,5 inhalable aerosol	12,5 inhalable aerosol			
Belgium	2,5	-			
Denmark	2,5	5			
European Union	2,5	-			
France	2,5	-			
Germany (AGS)	1 inhalable aerosol	4 inhalable aerosol (1)			
Germany (DFG)	1 inhalable aerosol	4 inhalable aerosol			
Hungary	2,5	10			
Ireland	2,5	-			
Italy	2,5	-			
Latvia	2,5	-			
Poland	1	3			
Singapore	2,5	-			
Spain	2,5	-			
Sweden	2	-			
Switzerland	1 inhalable aerosol	4 inhalable aerosol			
Turkey	2,5	-			
USA - OSHA	2,5	-			
United Kingdom	2,5	-			
Remarks:		·			
European Union Bold-type: Indicative Occupational Exposure Limit Values (2,3) and Limit Values for Occupational					
Exposure Binding, Occupational Exposure Limit Value-BOELV (for references see bibliography)					
(4) (for references see bibliography) ermany (AGS) (1) 15 minutes average value					
Germany (DFG) STV 15 minutes average value					
Germany (Dr G) 31 v 13 minutes av	crage value				

^{*(}IFA / GESTIS Stoffdatenbank, Internationale Grenzwerte für chemische Substanzen)

The above information is based on our current standard of knowledge and does not constitute any warranty of conditions of the product. The information does not form part of any contractual agreement. It remains the user's responsibility to adhere existing laws and regulations.