

Printing date: 19.06.18 Revision: 0 / 13.07.2016 Page 1 / 10

# 1. Identification of the product and of the company / undertaking

1.1. Product identifier: POLY-PTX® SC Fleece Belt

1.2 Use of the product

Recommended use: Non-woven abrasives for grinding / sanding different materials

1.3. Supplier: Gerd Eisenblätter GmbH

Jeschkenstraße 12d 82538 Geretsried

Phone: + 49 (0) 8171 / 9082 - 010

**Emergencies:** +49 (0) 8171 / 9082 – 010

# 2. Composition / Information on ingredients

The product contains the following ingredients which are classified according to Regulation (EC) Nr. 1272/2008 or for which a community occupational exposure limit value exists:

|                     |                |                | REACH Reg. N°  | Conc. (%)   | Classification a<br>(EC) N° 1272/2 | acc. to Regulation<br>2008 (CLP) |  |
|---------------------|----------------|----------------|----------------|-------------|------------------------------------|----------------------------------|--|
|                     | (if available) | (if available) | (if available) |             |                                    | Hazard<br>statements             |  |
| Aluminium Oxide     | 215-691-6      | 1344-28-1      | 215-691-6      | 35.0 – 50.0 | Not classified                     |                                  |  |
| Polyurethane, cured |                | mixture        |                | 15.0 - 35.0 | Not classified                     |                                  |  |
| Nylon Fibre         |                | mixure         |                | 15.0 – 35.0 | Not classified                     |                                  |  |
| Polyester Scrim     |                | mixture        |                | 5.0 – 15.0  | Not classified                     |                                  |  |

(For full text of H-phrases see section 16.)

Remark: No PDMS (silicone-oils) present in this product

# 3. Hazards identification

# 3.1. Hazard Classification

Not applicable

Abrasives are articles and not dangerous substances or mixtures according to the Regulation (EC) No. 1272/2008.

See also section 8 and 16.

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.



Trade Name: POLY-PTX® SC Fleece Belt Page 2 / 10

#### 3.2. Label elements

Abrasives are articles and not dangerous substances or mixtures and therefore no labelling is required according to the Regulation (EC) No. 1272/2008.

Signal word: Not applicable

Symbols: Not applicable

Pictograms: Not applicable

Notes to Physician: Not applicable

3.3. Other hazards

Not known

#### 4. First aid measures

See also section 8 and 16

### 4.1. Description of first aid measures

Inhalation: Not possible, due to the form of the product. If dust is inhaled, move person to fresh air.

If breathing is difficult, have qualified personnel administer oxygen. Seek medical attention

if irritation or other symptoms persist.

Skin contact: Wash skin with soap and water. If irritation or other symptoms develop, seek medical

attention.

Eye contact: Remove contact lenses if present and easy to do so. Flush eyes thoroughly with large

amounts of water, holding eyelids open. If irritation persists, seek medical attention.

Ingestion: Not likely, due to the form of the product. In the event of, do not induce vomiting. Rinse

mouth with water. Seek medical attention if a large amount is swallowed or if you feel

unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Not known, but dust may cause eye and respiratory irritation. Prolonged inhalation of high concentration of dust may cause adverse effects on the lungs.

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Not relevant. Treat symptomatically. Immediate medical attention should not be required.



Trade Name: POLY-PTX® SC Fleece Belt Page 3 / 10

# 5. Fire-fighting measures

#### 5.1. Suitable (and unsuitable) Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material and appropriate for surrounding area such as: water, foam, sand, powder or CO<sub>2</sub>

#### 5.2. Special hazards arising from the product

Toxic fumes (CO, CO<sub>2</sub>, NOx, HCN, aldehydes, including CH<sub>2</sub>O) may occur. Particulate matter and other organic compounds may be formed during combustion. Use respiratory protective equipment.

#### 5.3. Special protective equipment and precautions for fire-fighters

Extinguishing materials should be selected according to the surrounding area. Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus.

#### 6. Accidental release measures

## 6.1. Personal precautions, protective equipment, and emergency procedures

Wear appropriate respirator and protective clothing as needed to avoid eye contact and inhalation of dust.

# 6.2. Environmental precautions

Avoid contamination of water supplies and environmental releases. Report spills as required to authorities.

# 6.3. Methods and materials for containment and cleaning up

Carefully collect dry material, avoiding the creation of airborne dust. Place in a suitable container for disposal.

#### 7. Handling and storage

Follow instructions of grinding machine manufacturers and the relevant national regulations. In addition, observe the safety recommendations of the manufacturer.

### 7.1. Precautions for safe handling

Avoid breathing dust. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Wear suitable gloves, eye protection and appropriate protective clothing according to the operation. Wash thoroughly after handling. Consider potential exposure to components of the materials or coatings being processed. Refer to OSHA's substance specific standards for additional work practice requirements where applicable. Combustible dust could be generated during the normal use of this product. The dust could be explosive if in sufficient concentration with an ignition source.

Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions

# 7.2. Conditions for safe storage, including any incompatibilities

No special storage required.



Trade Name: POLY-PTX® SC Fleece Belt Page 4 / 10

# 8. Exposure controls / personal protection

# 8.1. Control parameters

Before grinding it is recommended to perform a risk assessment and to use personal protection equipment accordingly.

Note: Consider also components of base materials and coatings being processed.

Hazardous dust of the workpiece material may be generated during grinding and / or sanding operations. National regulations for dust exposure limit values have to be taken into consideration.

Occupational exposure limit values and / or biological limit values:

| Substance           | EC-No.          | CAS-No.          | Occupational limit value / PEL |        |              |    |             |     |              |             |
|---------------------|-----------------|------------------|--------------------------------|--------|--------------|----|-------------|-----|--------------|-------------|
|                     | (if aa.ilalala) | (:f :  -   -   - | Long term / TWA                |        |              |    |             |     |              |             |
|                     | (if available)  | (if available)   | mg/m³                          |        |              |    | ml/m³ (ppm) |     |              |             |
|                     |                 |                  | СН                             |        | USA<br>NISHO |    | СН          | GER | USA<br>NISHO | USA<br>OSHA |
| Aluminium Oxide     | 215-691-6       | 1344-28-1        | 3 a                            | 1.25 a | 5 a          | NA | NA          | NA  | NA           | NA          |
| Polyurethane, cured |                 | mixture          | NA                             | NA     | NA           | NA | NA          | NA  | NA           | NA          |
| Nylon Fibre         |                 | mixure           | NA                             | NA     | NA           | NA | NA          | NA  | NA           | NA          |
| Polyester Scrim     |                 | mixture          | NA                             | NA     | NA           | NA | NA          | NA  | NA           | NA          |

| Substance           | EC-No.                 | CAS-No.                | Occupational limit value / PEL |         |              |    |             |    |              |             |  |
|---------------------|------------------------|------------------------|--------------------------------|---------|--------------|----|-------------|----|--------------|-------------|--|
|                     | /: <b>f</b> : - - - -) | /: <b>f</b> : - - - -) | Short to                       | erm / S | STEL         |    |             |    |              |             |  |
|                     | (if available)         | (if available)         | mg/m³                          |         |              |    | ml/m³ (ppm) |    |              |             |  |
|                     |                        |                        | СН                             |         | USA<br>NISHO |    | СН          |    | USA<br>NISHO | USA<br>OSHA |  |
| Aluminium Oxide     | 215-691-6              | 1344-28-1              | NA                             | NA      | NA           | NA | NA          | NA | NA           | NA          |  |
| Polyurethane, cured |                        | mixture                | NA                             | NA      | NA           | NA | NA          | NA | NA           | NA          |  |
| Nylon Fibre         |                        | mixure                 | NA                             | NA      | NA           | NA | NA          | NA | NA           | NA          |  |
| Polyester Scrim     |                        | mixture                | NA                             | NA      | NA           | NA | NA          | NA | NA           | NA          |  |

| Substance           | EC-No.         |                |    | Peak limit<br>mg/m³ |              |    |        |
|---------------------|----------------|----------------|----|---------------------|--------------|----|--------|
|                     | (if available) | (if available) | СН | _                   | USA<br>NISHO |    | СН     |
| Aluminium Oxide     | 215-691-6      | 1344-28-1      | 10 | 10                  | NA           | 15 | GESTIS |
| Polyurethane, cured |                | mixture        | NA | NA                  | NA           | NA | GESTIS |
| Nylon Fibre         |                | mixure         | NA | NA                  | NA           | NA | GESTIS |
| Polyester Scrim     |                | mixture        | NA | NA                  | NA           | NA | GESTIS |



Trade Name: POLY-PTX® SC Fleece Belt Page 5 / 10

Abbreviation:

e: einatembar / inhalable a: alveoleongängig/ respirable NA: nicht zutreffend/ not applicable

**EUROP:** 

Longterm: The employee's average airborne exposure in any 8-hour work shift of a 42-hour work week which

shall not be exceeded.

Shortterm: Maximum exposure of four 15min periods per 8-hour shift, with at least 60 minutes between exposure

periods

USA:

PEL: Permitted Exposure Limits

TWA: The employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be

exceeded.

STEL: Maximum exposure of four 15min periods per 8-hour shift, with at least 60 minutes between exposure periods

#### 8.2. Exposure controls

# 8.2.1. Appropriate engineering controls

Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits.

#### 8.2.2. Personal Protective Equipment

#### 8.2.1.1. Respiratory protection:

Use respiratory protective equipment, type depends on specific application and material being ground. Consider the potential for exposure to components of the coatings or base material being processed in selecting proper respiratory protection. Refer to OSHA's specific standards for lead, cadmium, etc. where appropriate. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134 and ANSI Z88.2 or other applicable regulations and standards and good Industrial Hygiene practice.

#### 8.2.1.2. Hand protection:

Wear protective gloves to avoid skin abrasion when handling type depends on specific application and material being ground.

### 8.2.1.3. Eye protection:

Wear protective goggles with side shields or face shield type depends on specific application and material being ground. To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment.

#### 8.2.1.4. Hearing protection:

Use hearing protection type depends on specific application and material being ground.

### 8.2.1.5. Body protection:

Use protective clothing type depends on specific application and material being ground.



Trade Name: POLY-PTX® SC Fleece Belt Page 6 / 10

# 9. Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Appearance: solid

Odour: Solid abrasive product, no odor

Odor threshold: not applicable

pH: not applicable

Melting point: not applicable

Boiling point: not applicable

Flash point: not applicable

Evaportation rate: not applicable

Flammability

(solid, gas): not applicable

Flammable Limits (LEL): not applicable

Flammable Limits (UEL): not applicable

Vapour pressure: not applicable

Vapour density: not applicable

Specific gravity: not applicable

Solubility in water: not applicable

Solubility - non water -: not applicable

Partition coefficient

(n-octanol / water): not applicable

Autoignition

temperature: not applicable

Decomposition

temperature: not applicable

Viscosity: not applicable

#### 9.2. Other information

None.



Trade Name: POLY-PTX® SC Fleece Belt Page 7 / 10

#### 10. Stability and reactivity

#### 10.1. Reactivity

Product is stable when handled or stored correctly.

#### 10.2. Chemical stability

No decomposition in normal use.

# 10.3. Possibility of hazardous reactions

No dangerous reactions known.

#### 10.4. Conditions to avoid

Product is stable when handled or stored correctly. Avoid temperatures over 200°C for excessive periods.

#### 10.5. Incompatible materials

No dangerous reactions known.

# 10.6. Hazardous decomposition products

At temperatures exceeding 250° C hazardous or toxic decomposition products may be generated – see section 5.2

#### 11. Toxicological information

The information below may not be consistent with the material classification in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and / or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on acute effects of exposure

#### 11.1.1. Inhalation

Breathing dust may cause irritation to the nose, throat and upper respiratory tract.

# 11.1.2. Skin Contact

May cause abrasive skin irritation.

#### 11.1.3. Eye Contact

May cause abrasive irritation and injury.

#### 11.1.3. Ingestion

Not toxic. Swallowing may cause gastrointestinal disturbances.

#### 11.1.4. Chronic Health Effects

Prolonged inhalation of respirable dust may cause adverse lung effects. Most of the dust generated during abrasive processes is from the base material being processed and the potential hazard from this exposure must be evaluated.

#### 11.1.5. Sensitization

Aluminum oxide was negative in a sensitization studies in guinea pigs.

#### 11.1.6. Germ Cell Mutagenicity

This product is not expected to present a risk of genetic damage. Negative in a bacterial recombination assay.



Trade Name: POLY-PTX® SC Fleece Belt Page 8 / 10

#### 11.1.7. Reproductive Toxicity

No specific data is available; however, this product is not expected to present a risk of adverse reproductive or developmental toxicity.

# 11.1.8. Carcinogenicity

| Name            | Route     | Species           | Value            |
|-----------------|-----------|-------------------|------------------|
| Overall product | Ingestion | No data available | not carcinogenic |

#### 11.1.9. Acute toxicity values

| Name            | Route     | Species           | Value                        |
|-----------------|-----------|-------------------|------------------------------|
| Overall product | Ingestion | No data available | calculated ATE > 5,000 mg/kg |

ATE = acute toxicity estimated

#### 12. **Ecological information**

No adverse effects on aquatic organisms are expected. However, consideration must be given to potential environment effects of the base material being processed.

#### 12.1. Toxicity

No effects known.

# 12.2. Persistence and degradability

No biodegradable potential known.

#### 12.3. Bioaccumulative potential

No potentials known.

# 12.4. Mobility in soil

No potentials known.

#### 12.5. Results of PBT and vPvB assessment

Not relevant.

#### 12.6. Other adverse effects

No effects known. Valuated.

#### **Disposal considerations** 13.

# 13.1. Waste treatment methods

Dispose in accordance with all local, state and national regulations. Local regulations may be more stringent than regional and national requirements. It is the responsibility of the waste generator to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

#### 13.1.2. Product

Follow national and regional regulations.

Due to the ingredients and properties disposal as non hazardous waste (2000/532/EC) is possible if no hazardous materials are added to the abrasives. (EWC - Nr. 120121)

### 13.1.3. Packing

Follow national and regional regulations



Trade Name: POLY-PTX® SC Fleece Belt Page 9 / 10

### 14. Transport information

The product is not covered by international regulation on the transport of dangerous goods.

|     | UN Number | Proper shipping name | Hazard Class | Packing Group | Environmental Hazard |
|-----|-----------|----------------------|--------------|---------------|----------------------|
| DOT | None      | Not Regulated        | None         | None          |                      |
| TDG | None      | Not Regulated        | None         | None          |                      |

# 14.1. Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

Not determined.

# 14.2. Special precautions

None identified.

#### 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the product

#### 15.1.2. European Regulation

No specific labelling requirements under respective EC directives.

#### 15.1.3. US Federal Regulations

Contact "Gerd Eisenblätter GmbH" for more information.

### 15.1.3.1 CERCLA Hazardous Substances (Section 103)/RQ:

This product is not subject to CERCLA release reporting. Many states have more stringent spill reporting requirements. Report spills in accordance will all applicable regulations.

#### 15.1.3.2. SARA Hazard Category (311/312)

| Fire Hazard                | No |
|----------------------------|----|
| Sudden Release of Pressure | No |
| Reactivity                 | No |
| Acute Health               | No |
| Chronic Health             | No |

#### 15.1.3.3. EPA SARA 313

This product contains the following chemicals regulated under SARA Title III, section 313

| Substance      | CAS-N°    | Procent |
|----------------|-----------|---------|
| Aluminum Oxide | 1344-28-1 | 100%    |

# 15.1.3.4. California Proposition 65

This product is not known to contain regulated chemicals. Dust created from abrasive processing may contain chemicals known to cause cancer, birth defects or other reproductive harm.

#### 15.1.3.5. EPA TSCA Inventory

All of the components of this product are listed on the TSCA inventory.

## 15.2. Chemical safety assessment

Not relevant.



Trade Name: POLY-PTX® SC Fleece Belt Page 10 / 10

#### 16. Other information

| NFPA RATING (NFPA 704) | FIRE | 1 | HEALTH | 1 | INSTABILITY     | 0 |
|------------------------|------|---|--------|---|-----------------|---|
| HMIS RATING            | FIRE | 1 | HEALTH | 1 | PHYSICAL HAZARD | 0 |

The information given is based on current knowledge. Products are described in term of their safety data. The data does not signify any warranty with regard to the products properties.

Further information relating to the use of the product can be obtained from the technical datasheets.

The product should only be used for the stated application or applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet.